

Cobots with 7 axes – shaping the future of flexible automation



How can you outsmart the competition? Simply automate!

A payload of 5 to 18 kg and a reach of 850 to 1800 mm – all delivered at joint speeds of up to 225 degrees per second: Our five lightweight 7-axis robots are ready to go to work in virtually no time – at companies of all sizes.

Our concept of simply automate comes from our

Our concept of simply automate comes from our unique benefits:

- Plug-in configuration
- Intuitive programming with a phone-like user interface
- Easy relocation within a factory thanks to the lightweight design

Your major benefit: Every cobot made by Kassow Robots has a 7th axis. This axis gives our cobots the highest possible degree of freedom. The robot's arm mimics the dexterity of the human arm. A feature that enables it to reach around corners.

From standard to sophisticated tasks, our cobots are prepared to perform the infinite number of jobs required in factory automation operations (see page 4).





Kassow Robots: Product Family

Reach/Payload

Great potential for beginners and pros



- Providing you with our modular platform CBuns for capability extensions
- Seamless end-of-arm tooling that is easy to install and configure
- Option to extend any kind of software based on efficient C/C++ code using robot API
- Option to prepare and import your own custom code into our system
- 500Hz servo loop
- ROS integration

3

















Cobots with maximum dexterity in action

Pick & place, machine tending, welding, gluing, labelling, palletizing: From small batch to 24/7 mass production, our lightweight robots can perform virtually any production task

The special kinetics created by the 7th axis allows Kassow Robots to outclass conventional cobots.

Kinematic examples:

- Any predefined path straight, zigzag, or curved can be followed without stopping and at a pre-set speed.
- The extraordinary maneuvrability allows the cobots to be used in the most confined spaces – an invaluable benefit in the push to automate existing production.



Gaining far more production with 7 axes

Your added value created by our lightweight robots

- Great maneuvrability & around-the-corner reach
 You can use the robot's arms in extremely confined
 spaces and profit from the tremendous flexibility
 created by the 7th axis!
- Easy programming & operations
 Divorce yourself from robot experts program and operate the cobots yourself!
- High flexibility & fast relocation
 Use the cobots in different places within your production facilities the cobots' light weight and the plug and play approach makes it possible!
- Employees & cobots team up
 Delegate the repetitive and unsafe jobs to your robot colleagues and allow your employees to generate more added value elsewhere!
- Fast ROI & more satisfied employees
 Our cobots pay for themselves quickly boost your competitiveness with their high productivity!

Robots that can share work space with humans without being placed in safety enclosures are called collaborative robots or simply "cobots." In the process known as human-robot collaboration (HRC), a robot's various skills (e.g., strength, precision, and stamina) are combined with the strengths of humans (e.g., make decisions, evaluate alternatives). As a result, robots and humans can work near one another. The entire process is safe: if, for instance, a cobot encounters a barrier, it will shut off automatically.



"Strong, Fast, Simple" and lots of added value created by the 7th axis – company founder Kristian Kassow continues to look out for the customers.




Sales Director Dieter Pletscher shows just how easy it is to operate a cobot. "It reminds me of a smartphone."

 $\mathbf{1}$

Dimensions and special product features


Robot head & ports


All cobot models



Dimensions of the base plate

KR810, KR1205







Connectivity

to end-of-arm tool.

- Three I/O ports with 24V power
- Ethernet port (ModBus TCP)
 Our cobots can be connected directly



Free drive button

- Flexible waypoint programming
- Operation without a user panel



Are you interested in flexible automation?

Contact us if you have any questions about our cobots or have specific projects in mind!

At a glance: Technical specifications

General specifications	KR810	KR1018	KR1205	KR1410	KR1805			
Reach (mm)	850	1000	1200	1400	1800			
Payload (kg)	10	18	5	10	5			
Weight (kg)	24	34	25	35	38			
Joint speed (deg/s)	225	163/225	225	163/225	163/225			
Joint ranges (deg)	J2 and J4: -70°/+180°; J1, J3, J5, J6 and J7: ±360°							
Brakes on joints	Yes	Yes	Yes	Yes	Yes			
Absolute encoders on joints	Yes	Yes	Yes	Yes	Yes			
Repeatability (mm)	+/- 0.1	+/- 0.1	+/- 0.1	+/- 0.1	+/- 0.1			
Degrees of freedom	7	7	7	7	7			
Footprint (mm)	130 × 130	160 × 160	130 × 130	160 × 160	160 × 160			
Operating temperature (C°)	0-45	0-45	0-45	0-45	0-45			
Body material	Anodized aluminum							
Protection rating	IP54	IP54	IP54	IP54	IP54			

Controller	KR810	KR1018	KR1205	KR1410	KR1805
Digital outputs 24V (pcs)	8	8	8	8	8
Relay outputs (pcs)	4	4	4	4	4
Digital inputs 3–30V (pcs)	16	16	16	16	16
Analogue I/O 0-10V (pcs)	2/2	2/2	2/2	2/2	2/2
Analogue I/O 4-20mA (pcs)	2/2	2/2	2/2	2/2	2/2

Power	KR810	KR1018	KR1205	KR1410	KR1805
Power consumption (with max. load; W)	400-600	400-1200	400-600	400-1200	400-1200
Supply voltage (VAC)	100-120 or 200-240				
Supply current (A)	16	16	16	16	16
Supply frequency (Hz)	50/60	50/60	50/60	50/60	50/60
Max speed (mm/s)	1200/1800	2000/2400	1200/1800	2000/2400	2000/2400
Sound level (dB)	<65	<65	<65	<65	<65

7 Axes · Collaborative · Strong · Fast · Simple · Flexible · Danish



"Strong, Fast, Simple": With this motto in mind, the Danish entrepreneur Kristian Kassow has developed five unique, efficient, lightweight robots with 7 axes. Manufactured in Copenhagen, KR cobots are extremely strong and fast, despite their long reach. They offer a payload of up to 18 kilograms, a reach of up to 1800 millimeters, and a speed of up to 225 degrees per second. Their exceptional maneuvrability enables industrial companies to automate production processes even in the most confined areas. The cobots are operated and

programmed with the help of teach pendants developed on the basis of widely used tablet technologies. It is an intuitive process and can be done by anyone – a feature that creates more independence and cost efficiency.

Kassow Robots made its first public appearance in 2018. In late April 2022, Bosch Rexroth became the company's new majority owner. Founder Kristian Kassow is now co-owner and will continue to serve as CFO of Kassow Robots.

Extensive Partner Network – reliable partners

Did you know that Kassow Robots has developed an extensive network of business partners across four continents and 30 countries and is continuously expanding its network?

Our partners are from medium-sized enterprises, speak the language of our end customers, and are available to assist them even after the purchase of

The Kassow Robots partner network and we look forward to your request: www.kassowrobots.com/partner

Your Local Kassow Robots Partner



MEG MECHANICA EQUIPMENT GROUP 6

SERVICE & SUPPORT

Wangara, WA +61 8 6314 1111 support@automation-control.com.au automation-control.com.au